

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

E200GL HARDENER

UFI: AFW2-0G30-NF8Y-GC5J

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Adhesives, sealants

Uses advised against

Any use not mentioned in the product data sheet.

1.3. Details of the supplier of the safety data sheet

Company name:	HP-Textiles GmbH	
Street:	Otto-Hahn-Str. 22	
Place:	D-48480 Schapen	
Telephone:	+49 (0) 5905 94598-70	Telefax: +49 (0) 5905 94598-74
e-mail:	produktsicherheit@hp-textiles.com	
Internet:	www.hp-textiles.com	
Responsible Department:	Safety department	

1.4. Emergency telephone number: +49 (0) 151 5473 5568 (08:00 a.m. - 03:00 p.m.)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Acute Tox. 4; H302
Skin Corr. 1B; H314
Eye Dam. 1; H318
Skin Sens. 1; H317
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

1,4-bis(aminocyclohexyl)methane
3-aminomethyl-3,5,5-trimethylcyclohexylamine
Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia

Signal word: Danger**Pictograms:****Hazard statements**

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 2 of 13

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor. Store
P405	locked up.
P501	Dispose of contents/container to hazardous waste.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Hazardous components**

CAS No	Chemical name	Quantity
	EC No Index No REACH No	
	Classification (GB CLP Regulation)	
1761-71-3	1,4-bis(aminocyclohexyl)methane	25 - 50 %
	217-168-8 01-2119541673-38	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1, STOT RE 2; H302 H314 H318 H317 H373	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25 - 50 %
	220-666-8 612-067-00-9 01-2119514687-32	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A; H302 H314 H318 H317	
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	25 - 50 %
	618-561-0 01-2119557899-12	
	Skin Corr. 1C, Eye Dam. 1, Aquatic Chronic 3; H314 H318 H412	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1761-71-3	217-168-8	1,4-bis(aminocyclohexyl)methane	25 - 50 %
		oral: ATE = 500 mg/kg	
2855-13-2	220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25 - 50 %
		inhalation: LC50 = >5,01 mg/l (dusts or mists); oral: ATE 1030 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100	
9046-10-0	618-561-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	25 - 50 %
		inhalation: LC50 = [0,74] mg/l (vapours); dermal: LD50 = 2980 mg/kg; oral: LD50 = 2885 mg/kg	

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 3 of 13

4.1. Description of first aid measures**General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of respiratory tract irritation, consult a physician. In the case of lung irritation: Primary treatment using corticoide spray, eg. Auxiloson spray, Pulmicort-dosage-spray. (Auxiloson and Pulmicort are registered trademarks.)

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Observe risk of aspiration if vomiting occurs. Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Sand. Foam. Carbon dioxide (CO₂). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂)

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Wear personal protection equipment (refer to section 8).
Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 4 of 13

Treat the recovered material as prescribed in the section on waste disposal.
Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Wear suitable protective clothing. (See section 8.)

Conditions to avoid: aerosol or mist formation

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

When using do not eat, drink or smoke.

Further information on handling

Advices on general occupational hygiene: See section 8.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Organic peroxides. Self-reactive substances and mixtures. Radioactive substances. Infectious substances.

Further information on storage conditions

Recommended storage temperature: 20°C

Protect against: frost. UV-radiation/sunlight. heat. Humidity

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia			
Worker DNEL, long-term		inhalation	systemic	1.36 mg/m³
Worker DNEL, long-term		dermal	systemic	2.5 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 5 of 13

PNEC values

CAS No	Substance	
Environmental compartment		Value
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	
Freshwater		0.015 mg/l
Marine water		0.014 mg/l
Freshwater sediment		0.132 mg/kg
Marine sediment		0.125 mg/kg
Secondary poisoning		6.93 mg/kg
Micro-organisms in sewage treatment plants (STP)		7.5 mg/l
Soil		0.018 mg/kg

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye/face protection. BS/EN 166

Hand protection

Wear suitable gloves.

Suitable material:

FKM (fluororubber). - Thickness of glove material: 0,4 mm

Breakthrough time \geq 8 h

NBR (Nitrile rubber). - Thickness of glove material: 0,35 mm

Breakthrough time \geq 8 h

PVC (Polyvinyl chloride).

Breakthrough time \geq 8 h

The selected protective gloves have to satisfy the specifications of EU Directive EC/2016/425 and the standard EN 374 derived from it.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Suitable protective clothing: Lab apron.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

-Exceeding exposure limit values

-Insufficient ventilation and aerosol or mist formation

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type A-P2

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates)

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 6 of 13

that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	yellowish
Odour:	characteristic

Test method**Changes in the physical state**

Melting point/freezing point:	No information available.
Boiling point or initial boiling point and boiling range:	>200 °C
Sublimation point:	No information available.
Softening point:	No information available.
Pour point:	No information available.
Flash point:	>100 °C

Flammability

Solid/liquid:	No information available.
Gas:	No information available.

Explosive properties

none

Lower explosion limits:	1,2 g/m ³
Upper explosion limits:	13 g/m ³
Auto-ignition temperature:	365 °C DIN 51794

Self-ignition temperature

Solid:	No information available.
Gas:	No information available.

Decomposition temperature:	No information available.
----------------------------	---------------------------

pH-Value:	No information available.
-----------	---------------------------

Viscosity / dynamic: (at 25 °C)	50 - 200 mPa·s
------------------------------------	----------------

Viscosity / kinematic:	No information available.
------------------------	---------------------------

Flow time:	No information available.
------------	---------------------------

Water solubility:	almost immiscible OECD 105
-------------------	----------------------------

Solubility in other solvents

No information available.

Partition coefficient n-octanol/water:	No information available.
--	---------------------------

Vapour pressure: (at 20 °C)	<1 hPa DIN 51640
--------------------------------	------------------

Vapour pressure: (at 50 °C)	No information available. DIN 51754
--------------------------------	-------------------------------------

Density (at 23 °C):	0,97 g/cm ³ ASTM D 1296
---------------------	------------------------------------

Bulk density:	No information available. ISO 1183 (A)
---------------	--

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 7 of 13

Relative vapour density:

No information available.

9.2. Other information**Information with regard to physical hazard classes**

Sustaining combustion:

No data available

Oxidizing properties

none

Other safety characteristics

Solvent separation test:

No information available.

Solvent content:

No information available.

Solid content:

100 %

Evaporation rate:

No information available.

Further Information**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Refer to chapter 10.5.

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight. heat.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong.

10.6. Hazardous decomposition productsIn case of fire may be liberated: Carbon monoxide Carbon dioxide (CO₂)**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Toxicokinetics, metabolism and distribution**

No information available.

Acute toxicity

Harmful if swallowed.

ATEmix calculated

ATE (oral) 804,7 mg/kg

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1761-71-3	1,4-bis(aminocyclohexyl)methane				
	oral	ATE 500 mg/kg			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	ATE 1030 mg/kg			
	inhalation (4 h) dust/mist	LC50 >5,01 mg/l	Rat.	ECHA Dossier	
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia				
	oral	LD50 2885 mg/kg	Rat	ECHA Dossier	
	dermal	LD50 2980 mg/kg	Rabbit.	ECHA Dossier	
	inhalation vapour	LC50 [0,74] mg/l	8 h Rat	ECHA Dossier	

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effectsMay cause an allergic skin reaction. (1,4-bis(aminocyclohexyl)methane;
3-aminomethyl-3,5,5-trimethylcyclohexylamine)**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (1,4-bis(aminocyclohexyl)methane)

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1. Toxicity**

The product has not been tested.

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine					
	Acute fish toxicity	LC50	110 mg/l	96 h	Leuciscus idus	ECHA Dossier
	Acute algae toxicity	ErC50	>50 mg/l	72 h	Desmodesmus subspicatus	ECHA Dossier
	Acute crustacea toxicity	EC50	23 mg/l	48 h	Daphnia Magna	ECHA Dossier
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia					
	Acute fish toxicity	LC50	>15 mg/l	96 h	Oncorhynchus mykiss	ECHA Dossier
	Acute algae toxicity	ErC50	141,72 mg/l	72 h	Skeletonema costatum	ECHA Dossier
	Acute crustacea toxicity	EC50	418,34 mg/l	48 h	Acartia tonsa	ECHA Dossier
	Algae toxicity	NOEC	100 mg/l	3 d	Skeletonema costatum	ECHA Dossier
	Crustacea toxicity	NOEC	200 mg/l	2 d	Acartia tonsa	ECHA Dossier

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	8%	28	ECHA Dossier
	Not readily biodegradable (according to OECD criteria)			
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia			
	OECD Guideline 301 B	0%	28	ECHA Dossier
	Not easily bio-degradable (according to OECD-criteria).			

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0,99
9046-10-0	Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	1,344

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 10 of 13

disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

200127 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); paint, inks, adhesives and resins containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 2735

14.2. UN proper shipping name:

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONDIAMINE)

14.3. Transport hazard class(es):

8

14.4. Packing group:

III

Hazard label:

8



Classification code:

C7

Special Provisions:

274

Limited quantity:

5 L

Excepted quantity:

E1

Transport category:

3

Hazard No:

80

Tunnel restriction code:

E

Inland waterways transport (ADN)**14.1. UN number or ID number:**

UN 2735

14.2. UN proper shipping name:

POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONDIAMINE)

14.3. Transport hazard class(es):

8

14.4. Packing group:

III

Hazard label:

8



Classification code:

C7

Special Provisions:

274

Limited quantity:

5 L

Excepted quantity:

E1

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 11 of 13

Marine transport (IMDG)

14.1. UN number or ID number: UN 2735
14.2. UN proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONDIAMINE)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
 Hazard label: 8



Marine pollutant: NO
 Special Provisions: 223, 274
 Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2735
14.2. UN proper shipping name: POLYAMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONDIAMINE)
14.3. Transport hazard class(es): 8
14.4. Packing group: III
 Hazard label: 8



Special Provisions: A3 A803
 Limited quantity Passenger: 1 L
 Passenger LQ: Y841
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 852
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 856
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Safe handling: see section 7
 Personal protection equipment: see section 8

14.7. Maritime transport in bulk according to IMO instruments

not relevant

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Additional information

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 12 of 13

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (amended by Regulation (EU) No 2020/878)

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

REACH 1907/2006 Appendix XVII, No (mixture): 3

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

1,4-bis(aminocyclohexyl)methane

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia

SECTION 16: Other information**Changes**

Rev. : 5,0 - Initial release 08.11.2022

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of substances and mixtures

DNEL: Derived No Effect Level

d: day(s)

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

ECHA: European Chemicals Agency

EWC: European Waste Catalogue

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

h: hour

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NLP: No-Longer Polymers

N/A: not applicable

OECD: Organisation for Economic Co-operation and Development

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

REACH: Registration, Evaluation, Authorisation of Chemicals

SVHC: substance of very high concern

TRGS: Technische Regeln für Gefahrstoffe

UN: United Nations

Safety Data Sheet

according to UK REACH Regulation

E200GL HARDENER

Revision date: 08.11.2022

Product code: 153

Page 13 of 13

VOC: Volatile Organic Compounds

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

Health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data and / or calculated and / or estimated.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)